

QUIETO Petals kit



AESTHETIC BENEFITS

Island of 3 geometric unicolour shapes Easily adjustable in height

TECHNICAL BENEFITS

Certifed acoustic performance (α_w = 1) NRC = 1.00 - SAA = 1.00 - CLASS B Fire-rated (Twist Melange): ASTM E84 CLASS B CAN/ULC S102


No rotation of the panel on itself thanks to 3 suspension points (2 ceiling fixing points) Product adaptation on demand



OEKO-TEX® CONTIGENCE IN TEXTILES STANDARD 100 since


QUIETO Petals kit

Easy to install, the QUIETO Petals kit brings a light and airy design to spaces while significantly reducing the reverberation of sound in the room. It is made up of acoustic panels cut from the same fabric color in 3 different sizes. The suspension system guarantees no rotation and easy adjustment of the height of each petal.



Please note that samples finishes are look different from the real coating finishes.

QUIETO PETALS KIT DIMENSIONS & AVERAGE WEIGHTS



	PETAI = 3 acous	AVERAGE WEIGHTS Without packaging		
1	38½" x 27½" x 2"	±977 x 693 x 50mm	3.5lbs	1,6kg
2	29½" x 20¾" x 2"	±749 x 525 x 50mm	1.75lbs	0,8kg
3	25¼" x 18¾" x 2"	±642 x 475 x 50mm	1.5lbs	0,6kg
1	Making a surface equiv ≈ surface of 3 standar	6.5lbs	3kg	

MYO_FT-09.2021

myo-solution.com

QUIETO PETALS KIT

The absorption coefficient αw (alpha w) is used to characterise a product's performance through a unique value. It ranges between 0 (product totally reflective) and 1 (product totally absorbent). The more α_w is closer to 1, the better the absorption.

f (Hz)	α _s	αS						
		1,20						595x595x50mm
100	0,35							23 ³ / ₈ " x 23 ³ / ₈ " x 2"
125	0,52	•				Ī		
160	0,88	1,00	\mathbf{V}					
200	0,84							
250	0,99	0,80						
315	1,07							
400	1,06				α _w = 1			
500	0,95	0,60			NRC=1.00			
630	0,88				SAA=1.00			
800	0,93	0,40			3AA-1.00			
1000	1,03	6,10						
1250	0,98							
1600	1,09	0,20						
2000	1,07							
2500	1,08	0,00					f	(Hz)
3150	1,10		500 1000	1500 2000	2500 3000	3500 4000	4500 5000	
4000	1,11						CETD	
5000	1,18						le lutur en construction	
	NF EN ISO 354							

QUIETO PETALS KIT

Fixed to the ceiling, each of the petals is equipped with 3 suspension points (to prevent rotations) for 2 fixing ceiling points.

	FIXING SYSTEMS (references)	Estimated installation time
HORIZONTAL SUSPENSION Fixing with cables from the ceiling. Provided cable length: 2m	Plaster or wood: KITFIHORPBPETL	30mn to 45mn (depending on the support)